

• *VB-FullAir*



The Nissan Primastar X-83



with VB-FullAir rear axle air suspension

Nissan Primastar X-83 also available with VB-FullAir rear axle air suspension

The Nissan Primastar is available with rear axle air suspension. The Primastar is extremely suited for the use of air suspension systems and our VB-FullAir-2C is available for new and used vehicles. This newly developed rear axle air suspension, from VB-Airsuspension, is available as an after-market option through the Nissan network.



VB-FullAir 2C system

The VB-FullAir, a full-air rear-axle air-suspension, has an electronic system named VB-ASCU (VB-Air Suspension Control Unit), which automatically monitors and adjusts the height level of the vehicle. This constant monitoring and adjusting (independent of the load, in the longitudinal and lateral direction and relatively independent of centre gravity height) will automatically contribute to a safe vehicle behaviour and a better comfort. The vehicle may not be overloaded.

Changing height

The vehicle level can be changed manually with the standard handheld when the vehicle stands still; therefore lowering of the chassis/ load platform is one of the systems standard possibilities.



Software

The electronic part of the rear axle air suspension is compatible with the vehicle's main electrical system. Various software variants create the possibility to adapt the VB-FullAir 2C air-suspension to the specific use of the vehicle.



Advantages VB-FullAir 2C::

- Improved suspension comfort
- Constant ride height
- Improved road handling and stability
- Increased protection of vulnerable / sensitive goods
- Less impact for passengers
- Kneeling facility
- Less wear of tyres / brakes
- Environmentally friendlier, less CO2 emission

Market circumstances

The Nissan Primastar X-83 will be used for a wide range of individual needs and market circumstances where air suspension is essential. For example: passenger transport, disabled persons transport, rescue vehicles, motorhomes, car transporters and for the transport of shock-sensitive products. For these and more usages, and individual needs, our VB-FullAir-2C is the right solution.

Supply and service

Air-suspended Primastars can be supplied and serviced by VB-Airsuspension dealers and the Nissan dealer organisation.

VB-Airsuspension data:

	Van *
Standard driving height (unloaded)	560-580 mm
Standard driving height (max. load)	460-480 mm
Driving height with VB-FullAir-2C	570 mm
Highest position	+ 20 mm
Lowest position	-145 mm

* Van: floor height measured on the bottom at the rear doors

For more information: info@vbairsuspension.com

